


Code ST02	Project A47-A	Release E	TECHNICAL DATASHEET
---------------------	-------------------------	---------------------	----------------------------

ABSOLUTE MAGNETIC SENSOR CSA

GENERAL FEATURES

- Linear magnetic sensor, with direct reading of the absolute position.
- Resolutions up to 1 μm .
- Measuring length up to 30 000 mm.
- High-speed serial interface.
- Contactless reading.
- Warning indication through LED.
- Extremely easy and fast mounting of the entire measuring system, with wide alignment tolerances.
- Small size, to allow installation in narrow spaces.
- Option: 1 Vpp analog signal.
- Axial or radial cable output.



MECHANICAL AND ELECTRICAL CHARACTERISTICS

MECHANICAL	Cod. CSA	M
<ul style="list-style-type: none"> • Magnetic sensor with die-cast body. • Possibility to fix the magnetic sensor with M4 screws or with through M3 screws. • Wide alignment tolerances. • Robust sealed cable exit. 	Pole pitch	2+2 mm
	Incremental signal	sine wave 1 Vpp (optional)
	Resolution 1 Vpp	up to 1 μm *
	Repeatability	± 1 increment
	Signal period	2 mm
	Serial interface	SSI – BiSS
	Resolution absolute position	500 - 100 - 50 - 10 - 5 - 1 μm
	Accuracy	$\pm 15 \mu\text{m}$
	Measuring length ML	up to 30 000 mm
	Max. traversing speed	300 m/min **
	Vibration resistance (EN 60068-2-6)	200 m/s ² [55 ÷ 2 000 Hz]
	Protection class (EN 60529)	IP 67
	Operating temperature	0 °C ÷ 50° C
	Storage temperature	-20 °C ÷ 70° C
	Relative humidity	100%
	Power supply	5 ÷ 28 Vdc \pm 5%
	Current consumption	150 mA _{MAX} (with R = 120 Ω)
	Max. cable length	20 m ***
	Electrical connections	see related table
	Electrical protections	inversion of polarity and short circuits
	Weight	80 g

SIGNALS	CONDUCTOR COLOR
+ V	Brown
0 V	White
CK	Green
$\overline{\text{CK}}$	Yellow
D	Pink
$\overline{\text{D}}$	Grey
SCH	Shield

* Depending on CNC division factor.


** With a 1 μm resolution, the maximum traversing speed becomes 90 m/min.

*** Ensuring a minimum power supply of 5 V to the sensor, the maximum cable length can be extended to 50 m.

Code ST02	Project A47-A	Release E	TECHNICAL DATASHEET
---------------------	-------------------------	---------------------	----------------------------


OUTPUT SIGNALS

SSI Version



Interface	SSI Binary – Gray
Signals level	EIA RS 485
Clock frequency	0.1 ÷ 1.2 MHz
n	Position bit
Tc	12 ÷ 45 µs


BiSS C (unidirectional) Version



Interface	BiSS C unidirectional
Signals level	EIA RS 485
Clock frequency	0.1 ÷ 2 MHz
n	26 + 2 + 6 bit
Tc	12 ÷ 45 µs

CABLE

Serial output




In case of cable extension, it is necessary to guarantee:


- the electrical connection between the body of the connectors and the cables shield;
- a minimum power supply voltage of 5 V to the sensor.

SENSOR DIMENSIONS

AXIAL




RADIAL



values in mm	MP200A	MP200A + CV103	MP200A + SP202
s	1.3	1.6	2.1
d	0.3 ÷ 1	0.7 _{MAX}	0.2 _{MAX}

s = thickness
d = distance to be maintained between sensor and surface of the magnetic band (or eventual cover/support)

SENSOR ALIGNMENT TOLERANCES



ORDERING CODE

MODEL	POLE PITCH	RESOLUTION	CABLE OUTPUT	POWER SUPPLY	OUTPUT SIGNALS	INCREMENTAL SIGNAL	CABLE LENGTH, CABLE TYPE	CONNECTOR
CSA	M	1	A	528V	S0	V	M02 / S	SC

M = 2+2 mm
500 = 500 µm
100 = 100 µm
50 = 50 µm
10 = 10 µm
5 = 5 µm
1 = 1 µm

A = axial
R = radial

528V = 5 ÷ 28 V

S0 = SSI programmable
S1 = SSI binary
S2 = SSI binary+even parity
S3 = SSI binary+odd parity
S4 = SSI binary+error
S5 = SSI binary+even parity+error
S6 = SSI binary+odd parity+error
S7 = SSI Gray
B1 = BiSS binary

V = +1 Vpp
No cod. = no incremental signal

Mnn = length in m
M02 = 2 m (standard)
M50 = 50 m

R = 6 wires (only serial)
S = 10 wires (serial + analog)

SC = without connector
Cnn = progressive

Example **ABSOLUTE MAGNETIC SENSOR CSA M1A 528V S0 V M02 / S SC**